



TEGERA® 130

Heat-resistant glove, unlined, 0,7-0,8 mm, full grain goatskin, full grain goatskin, Cat. II, white, yellow, reinforced index finger, reinforced seams, elasticated 180°, for assembly work

PROPERTIES

High level of protection, extremely good fingertip sensitivity, durable, excellent fit

SPECIFICATION

TYPE OF GLOVE Hand protection against heat

CATEGORY Cat. II

SIZE RANGE 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Full grain goatskin

LINING Unlined

DEXTERITY 4

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

COLOUR White, yellow

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Thread

MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
7	130-7	7392626013070
8	130-8	7392626013087
9	130-9	7392626013094
10	130-10	7392626013001
11	130-11	7392626013018

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 130

FEATURES

Withstands contact heat up to 100°C, reinforced index finger, reinforced seams, reinforced thumb, withstands welding sparks and grinding splash

PRIMARY PROTECTION

Prevents risk of: burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Warm environments, harsh environments

PRIMARY AREAS OF USE

Assembly, engineering, hot work

PRIMARY INDUSTRIES OF USE

Metal fabrication, automotive

TYPE OF WORK

Precision work

2(3)

 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-01-05

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 130

EC TYPE EXAMINATION

Notified Body: 0493 Centexbel, Technologiepark 7, BE-9052 Zwijnaarde (Gent) Belgium

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	2	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-01-05

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com