



TEGERA® 17

Heat-resistant glove, fully lined, 1,2-1,4 mm, split grain cowhide of top quality, split grain cowhide of top quality, jersey, Cat. II, yellow, withstands contact heat up to 100°C, reinforced seams, elasticated 180°, for heavy work

PROPERTIES

High level of protection, good fingertip sensitivity, very durable, good fit

SPECIFICATION

TYPE OF GLOVE Hand protection against heat

CATEGORY Cat. II

SIZE RANGE 8, 10, 11

PALM MATERIAL Split grain cowhide of top quality

PALM THICKNESS 1,2-1,4 mm

BACK MATERIAL Split grain cowhide of top quality

LINING Fully lined

LINING MATERIAL Jersey

DEXTERITY 2

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 240-280 mm

COLOUR Yellow

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather 99%, natural latex 1%

INNER MATERIAL SPECIFICATION Cotton 100%

SIZE	ART. NO.	EAN NO.
8	17-8	7392626001787
10	17-10	7392626001794
11	17-11	7392626027459

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 17

FEATURES

Withstands contact heat up to 100°C, reinforced seams, flame retardant, withstands welding sparks and grinding splash

PRIMARY PROTECTION

Prevents risk of: burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Warm environments, harsh environments

PRIMARY AREAS OF USE

Engineering, mining

PRIMARY INDUSTRIES OF USE

Mining, automotive

TYPE OF WORK

Heavy work

 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-01-20

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE Cat. II



TEGERA® 17

EC TYPE EXAMINATION

Notified Body: 0493 Centexbel, Technologiepark 7, BE-9052 Zwijnaarde (Gent) Belgium

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	2	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	3	(4)

3(3)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-01-20