



## TEGERA® 8

Heat-resistant glove, unlined, 1,0 - 1,2 mm, full grain cowhide, split grain cowhide, Cat. II, white, yellow, withstands contact heat up to 100°C, reinforced seams, elasticated 180°, for allround work

### PROPERTIES

High level of protection, good fingertip sensitivity, durable, good fit

### SPECIFICATION

TYPE OF GLOVE Hand protection against heat and welding risks

CATEGORY Cat. II

SIZE RANGE 8, 10

PALM MATERIAL Full grain cowhide

PALM THICKNESS 1,0 - 1,2 mm

BACK MATERIAL Split grain cowhide

LINING Unlined

DEXTERITY 3

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

COLOUR White, yellow

PAIRS PER PACKAGE/CARTON 6/60

MATERIAL SPECIFICATION Leather 99%, natural latex 1%

SIZE	ART. NO.	EAN NO.
8	8-8	7392626000872
10	8-10	7392626000896

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



## TEGERA® 8

### FEATURES

Withstands contact heat up to 100°C, reinforced index finger, reinforced seams, withstands welding sparks and grinding splash

### PRIMARY PROTECTION

Prevents risk of, burn injuries, heat injuries, blisters, grazes, scratches, lacerations, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Warm environments, harsh environments

### PRIMARY AREAS OF USE

Engineering

### PRIMARY INDUSTRIES OF USE

Automotive

### TYPE OF WORK

Allround work

CE Cat. II



EN 12477 Type B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-01-05

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10






info@ejendals.com

order@ejendals.com

www.ejendals.com



CE Cat. II

 EN 388 3142
  EN 407 413X4X
  EN 12477
  Type B
 

## TEGERA® 8

### EC TYPE EXAMINATION

Notified Body: 0493 Centexbel, Technologiepark 7, BE-9052 Zwijnaarde (Gent) Belgium

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	2	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 12477:2001 Protective gloves for welders

Type B - Higher dexterity (with lower other performance)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-01-05